




The BERGER MANUFACTURING CO. CANTON, OHIO.





GENERAL OFFICES FACTORY AND MILLS. The BERGER MFG. CO., CANTON, O.

"CLASSIK" STEEL CEILINGS

CATALOGUE NO. 21

Showing all new and beautiful Designs and Individual Units in Stucco and Colonial effects, being thoroughly characteristic of their respective architectural periods and combining in the highest degree Artistic Harmony, Mechanical Perfection and Serviceability.

The Designs and Parts published in this Catalogue are supplementary to our already large and diversified line illustrated in Catalogues Nos. 12, 16 and 19.



These new and exclusive Patterns have been designed and created by our artists with the view of placing Berger's "CLASSIK" Steel Ceilings on an even higher plane of decorative art, and further increasing their mechanical and constructional advantages.

THE BERGER MANUFACTURING COMPANY CANTON, OHIO, U. S. A.

Copyrighted 1916 by The Berger Mfg. Co.

NEW YORK, Corner 22nd Street and 11th Avenue
PHILADELPHIA, PA, 16th Street and Washington Avenue
BOSTON, MASS, 160-166 Broadway Extension CHICAGO, ILL, 20 North Market Street

SAN FRANCISCO, CALIF., 1120 Mission Street ST. LOUIS, MO., 16 South 10th Street MINNEAPOLIS, MINN., 300-312 10th Avenue, South

Why "Classik" Steel Ceiling

Art in Steel Ceilings



HE Berger Manufacturing Company was the first to conceive the idea of producing metal ceilings which could be definitely classified as to style or period of decoration represented; correct, harmon-

ious, and appropriate throughout, yet embodying the flexibility and wide range of application which is such an important characteristic of Steel Ceilings.

Steel ceilings which had been previously produced were but a conglomerate mixture of incongruous styles. That objectionable characteristic was effectually removed when The Berger Manufacturing Company developed and placed upon the market their now well-known line of "Classik" Steel Ceilings.

Improvement (Bead and Button Construction)

The bead has been enlarged and lengthened and shaped to a half oval, adding strength and rigidity, as well as reinforcing the ceiling plates at joints. The top of the nailing button being depressed or countersunk, forms a self-centering, self-guiding and never-slip nailing point, acts as a guide for the erector in placing nail in the correct position and prevents slipping while driving, increasing the speed and efficiency of the ceiling erector.

Facilities

Although our equipment has always been the best that the mechanical world could produce we recently designed and made and installed a large number of special presses and new equipment in order to assure even a better product than has been possible heretofore. The beads and buttons are stamped and repressed in one operation, absolutely true and perfect, each piece made with absolute precision and accuracy, being an exact fac-simile of the next in length, in width, and in every detail of ornamentation. Every bead and button fitting accurately over underlapping bead and button, makes a tight and perfect fitting joint, thereby eliminating the calking or tamping of joints, which has been a decidedly expensive factor in the cost of erection.

Advantages

These special features will reduce the cost of erecting at least 25 per cent, as well as assuring the owner and architect that Berger's "Classik" Ceilings cannot be installed other than in a thorough and workmanlike manner.

Made from Guaranteed Full Weight No. 29 Gauge Steel. Resquared on all sides.

Service

Ours is recognized in the trade as the largest sheet metal works in the world, in which every operation is conducted for the production of high-grade iron and steel sheets and the products made therefrom "from the ore to the store."

The capacity of our manufacturing plant and the fact that we operate our own complete steel and sheet mills enable us to offer our patrons service which cannot be excelled, and we are prepared to fill orders promptly, either from our main office or our branches where a stock is maintained.

With our enormous output (resulting in a maximum shop economy), the complete service we render in connection with inquiries, the assistance of our corps of trained experts, together with the excellence of our material, we are able to offer to the discriminating buyer a proposition which will give full value for the money invested.

Instructions for Taking Measurements



E require but little information, easily obtainable, from which to prepare our drawings; but what we do need must be given accurately, otherwise the ceiling, when shipped, will not fit.


Make a simple outline sketch of the shape of the room, not necessarily to scale, and indicate the measurements from point to point, in figures. Subdivided measurements should always equal the total length or width of room.

Make notation of any spaces not to be covered.

It is very necessary that measurements above the top of window and door casings to the ceiling line be given so that a cornice or molding of proper depth for a desirable finish may be selected. The windows frequently extend so nearly to the ceiling line in business rooms that only a small cornice, or flat mold, can be used. This information should always be given, and can be indicated as in Figure 2.

Upon application, suggestive drawings and estimates will be prepared and submitted, free of charge, for the approval of the customer.

Kindly indicate preference as to designs or style of ornamentation desired, depth of cornice permissible, and height of ceiling. This will be much appreciated and assist us in the preparation of an artistic arrangement in harmony with your requirements, and of design applicable to the shape of the room.



What Our Prices are Based On



HE prices for ceiling and wall material are for No. 29 gauge steel, painted one good priming coat both sides, including special oval-head nails for the application of the metal only, wood brackets

for molding and cornice, properly packed for shipment.

The weight of ceiling and wall material packed for shipment is approximately 65 pounds per square, or 100 square feet.

Wood furring strips are never provided for unless specially ordered, then same are charged for extra.

Metal ceilings are shipped on basis of fourth-rate classification.

Terms to Responsible Parties

For material only: Sixty days net, or two per cent for cash within ten days from date of invoice.

For work installed: Net cash on completion.

Delays will be avoided if purchasers will furnish dependable references at time of placing their order.

To parties not responsible: Order should be accompanied with remittance equal to twenty-five per cent of the value of the purchase, the balance to be subject to our sight draft with bill of lading attached. When this method of payment is desired the purchaser should not fail to state through what bank he desires collection made.

Rules for Estimating Lump Sum Prices

For Ceiling: The area to be charged for is obtained by adding twice the vertical height of cornice from bottom of foot mold to the full length and breadth of room, and multiplying the length and breadth thus obtained together, making no deduction for any skylight, stairway, or for any other opening or obstruction measuring less than 50 square feet.

Example: If the room measures 20 x 60 feet and a cor-

nice of 12-inch depth is used on both sides and ends of room add 24 inches to both length and breadth, as follows:

 $22' \ 0'' \ x \ 62' \ 0'' = 13.64 \ Squares$

To compute approximate lump sum price, multiply the number of squares by the proper list price per square of the design selected, which is published in connection with the various sizes of rooms. Cornice Mitres and Mitre Leavare not included in design list prices and must be figured extra at their respective list prices and added to the price of Ceiling material as follows:

This estimate is based on a plain rectangular room 20 x feet without any exposed beams, or other irregularities, whi might change quantity of material and list price of design

Rooms which are sub-divided by one or more exposibeams will require more material and cornice mitres and ta a higher list price per square. Each space or sub-division should be figured as individual rooms, using list prices approached to such size spaces; then add sufficient quantity material to cover exposed sides and bottoms of beams a figure same at their individual list prices.

For Sidewall and Wainscoting: The area charged for is obtained by multiplying the belt measurement of the root by height from base of foot mold on cornice to baseboar making no deductions for any openings measuring less the 25 square feet, nor for larger openings more than for who sheets saved.

In computing this class of work the contractor must ma provisions in his price for loss of material from wastage, et

Rules for Billing Material Sold at a Discount from List

Ceiling, sidewall, and wainscoting plates, dadoes, borders, and fillers are sold by the square foot.

Cornices and moldings by the lineal foot.

Cornice mitres, mitre leaves, and connections by the piece. Center pieces and ornaments by the piece when made solid.

Rules for Billing Material Sold at a Net Price per Square

Figure all plates, cornices, moldings, etc., at their actual individual covering area, and stiling or filler at its full width, thus saving the loss in underlapping.

Directions for Applying Berger's Patent Steel Ceiling and Wall Finish

Before commencing the application of material, verify all measurements and study carefully working plan.

Working Plans: Proper working plans are supplied, which are prepared from information and measurements furnished. If incorrect information is furnished in the matter of measurements, location of stairways, skylights, or other obstructions, discrepancies will occur, for which we will not be responsible.

Our plans will show in detail the exact location of every piece of material. It is very important that the constructor carefully study the working drawings, and same should be thoroughly understood before commencing the work.

Leveling of Joists: With a straight-edge it can be determined whether furring down or leveling is necessary. This may be accomplished by nailing to the side of joists a strip of necessary thickness, or by setting wedges, as may be required, after ceiling furring strips have been leveled.

It is absolutely essential that furring strips lengthwise and crosswise of the room are centered exactly to the center of nailing points on ceiling plates.

From both ends of the room at points indicated on working plan as "starting line," strike a chalk line; this establishes a starting line from which to work. For Continuous Ceilings: Use the following rule for placing of wood furring strips; towit: Place the first wood strip on starting line, and parallel to the same place additional strips 12 inches on centers for plates of 6 or 12-inch multiple, and for such 24-inch multiple plates which are not sufficiently rigid to carry their own weight without buckling or sagging. For all other 24-inch multiple plates strip 24 inches on centers. Cross-furring or headers must be inserted at the end of each plate whether same be furnished in 2, 4, or 8-foot lengths. This method of furring excels methods formerly practiced, because it provides a solid foundation or backing for all nailing points and requires a less quantity of strips; also reduces to a minimum the labor required in the application of the materials.

Furring should always be placed at right angle with joists; cross-furring or headers parallel with joists.

Should wood strips be furnished in connection with metal ceilings, the necessary amount required will be based on the above method of construction.

For Panel Ceilings (Sunken Panels): Parallel to the first strip placed on "starting line" through the room, place additional strips according to the width of panels used. Crossfurring strips or headers must be placed at the end of each

5

of room

iply the re of the with the

Leave red exim f Ceiling

00 6 20 x 60 s, which


design exposed and take

division s applintity of

ged for he room eboard,

r wh

Constructional Drawing of Ceiling and Sidewalls



panel or last multiple thereof. For example, if the panels are in sheets 4 or 8 feet long, cross-furring is necessary at the end of sheet only. Furring strips lengthwise and crosswise the room are to be centered exactly on the center of nailing points in ceiling panels or plates.

Cornices and moldings are to be applied with the use of wood brackets furnished for that purpose, as shown by working drawings; one wood bracket to every 4-foot section of cornice or molding, and extra brackets for miters and connections. Brackets are used under laps only

All cornices and moldings should be applied to a chalk line so that the finished work may be absolutely straight and accurate.

Nail the foot of the cornice in position before nailing the top edge, so as to provide for the underlapping of filler if necessary. Stamped miters for inside and outside corners are furnished for certain coves and cornices, and can be used for right-angle miters only. Stamped miter leaves for inside and outside corners are furnished for certain covers and cornices, and may be used for irregular-angle miters.

For certain coves and cornices both stamped miters and leaves are furnished. For all other coves and cornices the ceiling constructor will make or cope the necessary miters as the work proceeds Working plans always indicate width of border, molding, filler, and projection of cornice, and this will guide the constructor in spacing furring strips to receive same.

Strike a chalk line in center of strip or "starting line" for guidance in placing the plates or panels perfectly straight and true.

Always commence the application of material at rear of room and work forward, when possible

Metal Sidewalls: The foregoing rules also govern in the application of metal sidewall material, for which furring strips are required when the work is done over plaster or studding; we, however, recommend the use of close sheathing for all continuous plates. When sunken panels are used, furring strips must be used of a size to carry the depth of panel.

If metal wainscoting is used, this should be applied first, then such other material as working plan calls for to make the finish above wainscoting.

Care should be taken to keep the work straight and true.

Sufficient allowance for cutting, underlapping, and wastage will be provided for. An extra charge will be made for any additional material required on account of incorrect information or measurements.


Wood Furring Strips

Furring strips of $\frac{7}{8}$ x $\frac{7}{8}$ -inch size are very satisfactory when working over plaster, but experienced ceiling constructors, when working over joists or studding, prefer $\frac{7}{8}$ x $\frac{11}{4}$ -inch size; they are less liable to split, and provide a rigid foundation for the nailing of metal; especially is this true when toe-nailing headers or cross-furring in position.

Wood furring strips are never provided for unless specifically ordered; then same are charged for extra, because users of this class of material can usually purchase, in their own city or vicinity, the necessary furring strips at satisfactory prices and save freight charges.

Wood furring strips of $\frac{7}{8}$ x $1\frac{1}{4}$ inches weigh about 18 pounds per 100 lineal feet.

Constructional Drawing of Ceiling and Sidewalls



panel or last multiple thereof. For example, if the panels are in sheets 4 or 8 feet long, cross-furring is necessary at the end of sheet only. Furring strips lengthwise and crosswise the room are to be centered exactly on the center of nailing points in ceiling panels or plates.

Cornices and moldings are to be applied with the use of wood brackets furnished for that purpose, as shown by working drawings, one wood bracket to every 4-foot section of cornice or molding, and extra brackets for miters and connections. Brackets are used under laps only.

All cornices and moldings should be applied to a chalk line so that the finished work may be absolutely straight and accurate

Nail the foot of the cornice in position before nailing the top edge, so as to provide for the underlapping of filler if necessary. Stamped miters for inside and outside corners are furnished for certain coves and cornices, and can be used for right-angle miters only. Stamped miter leaves for inside and outside corners are furnished for certain covers and cornices, and may be used for irregular-angle miters.

For certain coves and cornices both stamped miters and leaves are furnished. For all other coves and cornices the ceiling constructor will make or cope the necessary miters as the work proceeds. Working plans always indicate width of border, molding, filler, and projection of cornice, and this will guide the constructor in spacing furring strips to receive same.

Strike a chalk line in center of strip or "starting line" for guidance in placing the plates or panels perfectly straight and true.

Always commence the application of material at rear of room and work forward, when possible

Metal Sidewalls: The foregoing rules also govern in the application of metal sidewall material, for which furring strips are required when the work is done over plaster or studding; we, however, recommend the use of close sheathing for all continuous plates. When sunken panels are used, furring strips must be used of a size to carry the depth of panel.

If metal wainscoting is used, this should be applied first, then such other material as working plan calls for to make the finish above wainscoting.

Care should be taken to keep the work straight and true.

Sufficient allowance for cutting, underlapping, and wastage will be provided for. An extra charge will be made for any additional material required on account of incorrect information or measurements.

Wood Furring Strips

Furring strips of $\frac{7}{8}$ x $\frac{7}{8}$ -inch size are very satisfactory when working over plaster, but experienced ceiling constructors, when working over joists or studding, prefer $\frac{7}{8}$ x $\frac{11}{4}$ -inch size, they are less liable to split, and provide a rigid foundation for the nailing of metal; especially is this true when toe-nailing headers or cross-furring in position.

Wood furring strips are never provided for unless specifically ordered, then same are charged for extra, because users of this class of material can usually purchase, in their own city or vicinity, the necessary furring strips at satisfactory prices and save freight charges.

Wood furring strips of $\frac{7}{8}$ x $1\frac{1}{4}$ inches weigh about 18 pounds per 100 lineal feet.

Decorative Suggestions



HE color scheme of the rooms in which we live or work has an important bearing upon our comfort, happiness and health. The most pleasing and cheerful rooms are always those that have been

painted in harmonious and inspiring colors. Many otherwise beautiful steel ceilings fail in their decorative purpose because conflicting colors are used or the color scheme selected is not in harmony with the rest of the room or its furniture or fixtures. The ceiling and sidewalls cannot be treated independently without destroying the harmony of the room.

Choice of Colors

Seeming Effect on Dimensions of Rooms

In selecting a color scheme, it is well to bear in mind that certain colors have a curious effect upon the dimensions of a room. Red walls, for example, make a room look smaller. Blue, yellow, tan, gray and pink seem to increase its size. Green (unless very dark) and brown (unless very light) keep the walls "well in place" and have no apparent effect upon their dimensions.

The Possibilities of Color Combinations

Generally speaking, green is restful and soothing, dark blue depressing, and red stimulating; but when used in judicious combination with certain other colors, quite different effects may be obtained. Blue with green or certain tones of yellow is pleasing, while red walls in a dark room will so absorb the light as to make the room gloomy. Green is warm or cold according to the proportion of blue or yellow of which it is composed. Pure yellow is the most sunshiny color in existence.

If the ceiling is too high to be in good proportion to the size of the room, the ceiling color should be brought down to the bottom of the cornice. This will give a drop ceiling effect and apparently lower the ceiling. On the other hand, if the ceiling is very low the sidewall color should be carried well u onto the cornice and blend into the ceiling color.

Very tasteful and delicate effects may be obtained by com binations of old rose or grayish blues or grayish greens.

Colors with enough black in them to give a grayish tor make easily blended and harmonious effects.

Tans, greens and browns usually harmonize, as do blues ar

Green and red contrast agreeably, while red and orange class Do not attempt the use of a number of colors, as the difficu ties of combination increase with the number of colo Always avoid the bold striping of moldings, cornice or pa of other members; also eliminate, as much as possible, gau colors and the use of gold or silver bronze as these have tendency to detract from the dignified appearance of ceiling.

Choose Colors According to Location of Rooms

Discrimination should be shown in the choice of colors rooms in different locations. Grays, blues, greens and s browns are especially good where there is plenty of sunlig but grays and blues are too "cold" for rooms with north exposure. Greens, tans and warm browns are good when there is less sunlight, and yellows and tans are needed brighten up the sunless north rooms. In other words, sunny rooms must have colors that soften the glare warmth, while dark rooms need warm, bright tones.

Finish - Flat or Gloss

The most satisfactory and by far the prettiest finish is dead or flat finish now so popular. This flat paint or en possesses the quality of bringing the lines of "Classik" ceilings into harmonious relief, giving a beautiful pl effect, not otherwise obtainable, at a reasonable cost. paint is comparatively new and, in spite of the fact that steadily growing in popularity, there are many people who do

not understand what it really is.

Good flat paints are regular oil finishes, but do not produce the glossy appearance which gives that "cold" look to a room. They radiate light instead of absorbing it or throwing a harsh

glare into your eyes.

bluesa

ble, gaudese have

s and so of suchs h norther ood when

needed

cost ct that it

All of the leading paint manufacturers make a flat finish paint that is washable with ordinary soap and water, and inasmuch as Berger's "Classik" steel ceilings and sidewalls can be washed without injury to the metal, this soft, velvety finish is the more appropriate. It is really the essential finish to bring out the quiet and luxurious charms of our "Classik" designs in a pleasing and effective manner

White gloss enamel is appropriate for kitchens, bath rooms or hotels where frequent washing is the rule and a sanitary appearance is required. Appropriate patterns should be selected, which will permit of securing the best results through the use of this gloss finish. Such patterns are the flat designs with shallow panel plates or very simple ornamentation.

How to Paint

Preparation

Before applying any paint make sure that the surface to

be treated is in proper condition to receive the coating; that all dirt and grease have been removed; and if any slight openings are noticeable after the first coat of paint has been applied, they should be closed up securely by the painter or decorator, before applying the second or finishing coat, using cement, plaster of Paris or crack filler for that purpose.

Berger's "Classik" steel ceilings and sidewalls are painted by a brush process, receiving one coat of lead and oil paint of a light gray color before shipment. In some instances where dark colors are used they can be finished with one additional coat. However, most ceilings and walls are painted some light shade to give more light and cheerfulness to the room. Two coats are then necessary to give the proper finish. Two or three thin coats of paint are much better than one thick coat.

Paints Not to Use

Do not confuse calcimine or cold water paints with the regular finish flat paints. Cold water paints and calcimine should never be used on steel coilings as they are undesirable and will not give you satisfactory results. Your ceilings are an important part of your building and if the right kind of paint is used and properly applied, you will have a decorative effect very pleasing and of which you may well be proud.

A Perfect Fire Retardant

An official fire test was made at the Columbia University Fire Testing Station, Greenpoint, Brooklyn, N. Y., November 11, 1914, under the auspices of the fire underwriters, for the purpose of determining the comparative fire-resisting qualities of steel and wood-and-plaster ceilings Steel ceilings resisted 1,369° Fahr for 1 hour and 10 minutes (which was as long as the test lasted) Wood lath-and-plaster ceilings. on the other hand, collapsed in 12 minutes although exposed to only 849°

In other words, steel ceilings can be counted upon remaining in place from 5 to 6 times as long as a wood-lath-and-plaster ceiling

The advantages of Steel Ceilings over wood and plaster are obvious They give perfect protection against fire, water, dust, vermin and rodents, do not crack and collapse and never shrink or warp.

Steel Ceilings and Sidewalls completely satisfy the demand for a noncombustible, decorative and durable interior finish for all buildings of the higher type, whether public, churches, theaters, court houses, business blocks, stores, shops, etc., or private residences, garages, etc.

The favor with which Berger's "Classik" Steel Ceilings are regarded in this country and abroad has stimulated us to higher artistic efforts. Architects, builders and owners who desire the most artistic and durable finish for the interiors of their buildings will be sure to appreciate and profit by our endeavors.

The growth and development of the steel ceiling industry proves that the public has been prompt to appreciate and utilize the advantages of ceilings and sidewalls which are ornamental in design, perfect in construction, and combine safety with durability and satisfactory service. Not only does this hold good with new buildings, but the protest of the public is further expressed in the thousands of lath and plaster ceilings which are annually being replaced with Berger's "Classik" Steel Ceilings and Sidewalls.

Decorative Suggestions



HE color scheme of the rooms in which we live or work has an important bearing upon our comfort, happiness and health. The most pleasing and cheerful rooms are always those that have been

painted in harmonious and inspiring colors. Many otherwise beautiful steel ceilings fail in their decorative purpose because conflicting colors are used or the color scheme selected is not in harmony with the rest of the room or its furniture or fixtures. The ceiling and sidewalls cannot be treated independently without destroying the harmony of the room

Choice of Colors

Seeming Effect on Dimensions of Rooms

In selecting a color scheme, it is well to bear in mind that certain colors have a curious effect upon the dimensions of a room. Red walls, for example, make a room look smaller. Blue, yellow, tan, gray and pink seem to increase its size Green (unless very dark) and brown (unless very light) keep the walls "well in place" and have no apparent effect upon their dimensions.

The Possibilities of Color Combinations

Generally speaking, green is restful and soothing, dark blue depressing, and red stimulating; but when used in judicious combination with certain other colors, quite different effects may be obtained. Blue with green or certain tones of yellow is pleasing, while red walls in a dark room will so absorb the light as to make the room gloomy. Green is warm or cold according to the proportion of blue or yellow of which it is composed. Pure yellow is the most sunshiny color in existence.

If the ceiling is too high to be in good proportion to the size of the room, the ceiling color should be brought down to the bottom of the cornice. This will give a drop ceiling effect and apparently lower the ceiling. On the other hand, if the ceiling is very low the sidewall color should be carried well u onto the cornice and blend into the ceiling color.

Very tasteful and delicate effects may be obtained by com binations of old rose or grayish blues or grayish greens.

Colors with enough black in them to give a grayish ton make easily blended and harmonious effects.

Tans, greens and browns usually harmonize, as do blues an

Green and red contrast agreeably, while red and orange class Do not attempt the use of a number of colors, as the difficu ties of combination increase with the number of color Always avoid the bold striping of moldings, cornice or par of other members, also eliminate, as much as possible, gauc colors and the use of gold or silver bronze as these have tendency to detract from the dignified appearance of the ceiling

Choose Colors According to Location of Rooms

Discrimination should be shown in the choice of colors f rooms in different locations. Grays, blues, greens and so browns are especially good where there is plenty of sunligh but grays and blues are too "cold" for rooms with northe exposure. Greens, tans and warm browns are good whe there is less sunlight, and yellows and tans are needed brighten up the sunless north rooms. In other words, t sunny rooms must have colors that soften the glare a warmth, while dark rooms need warm, bright tones.

Finish—Flat or Gloss

The most satisfactory and by far the prettiest finish is t dead or flat finish now so popular. This flat paint or enan possesses the quality of bringing the lines of "Classik" st ceilings into harmonious relief, giving a beautiful plas effect, not otherwise obtainable, at a reasonable cost. F paint is comparatively new and, in spite of the fact that it steadily growing in popularity, there are many people who do

not understand what it really is.

Good flat paints are regular oil finishes, but do not produce the glossy appearance which gives that "cold" look to a room. They radiate light instead of absorbing it or throwing a harsh

glare into your eyes.

All of the leading paint manufacturers make a flat finish paint that is washable with ordinary soap and water, and inasmuch as Berger's "Classik" steel ceilings and sidewalls can be washed without injury to the metal, this soft, velvety finish is the more appropriate. It is really the essential finish to bring out the quiet and luxurious charms of our "Classik" designs in a pleasing and effective manner.

White gloss enamel is appropriate for kitchens, bath rooms or hotels where frequent washing is the rule and a sanitary appearance is required. Appropriate patterns should be selected, which will permit of securing the best results through the use of this gloss finish. Such patterns are the flat designs with shallow panel plates or very simple ornamentation.

How to Paint

Preparation

Before applying any paint make sure that the surface to

be treated is in proper condition to receive the coating; that all dirt and grease have been removed; and if any slight openings are noticeable after the first coat of paint has been applied, they should be closed up securely by the painter or decorator, before applying the second or finishing coat, using cement, plaster of Paris or crack filler for that purpose.

Berger's "Classik" steel ceilings and sidewalls are painted by a brush process, receiving one coat of lead and oil paint of a light gray color before shipment. In some instances where dark colors are used they can be finished with one additional coat. However, most ceilings and walls are painted some light shade to give more light and cheerfulness to the room. Two coats are then necessary to give the proper finish. Two or three thin coats of paint are much better than one thick coat.

Paints Not to Use

Do not confuse calcimine or cold water paints with the regular finish flat paints. Cold water paints and calcimine should never be used on steel ccilings as they are undesirable and will not give you satisfactory results. Your ceilings are an important part of your building and if the right kind of paint is used and properly applied, you will have a decorative effect very pleasing and of which you may well be proud.

A Perfect Fire Retardant

An official fire test was made at the Columbia University Fire Testing Station, Greenpoint, Brooklyn, N. Y., November 11, 1914, under the auspices of the fire underwriters, for the purpose of determining the comparative fire-resisting qualities of steel and wood-and-plaster ceilings. Steel ceilings resisted 1,369° Fahr. for 1 hour and 10 minutes (which was as long as the test lasted). Wood-lath-and-plaster ceilings, on the other hand, collapsed in 12 minutes although exposed to only 849°


In other words, steel ceilings can be counted upon remaining in place from 5 to 6 times as long as a wood-lath-and-plaster ceiling.

The advantages of Steel Ceilings over wood and plaster are obvious. They give perfect protection against fire, water, dust, vermin and rodents, do not crack and collapse and never shrink or warp.

Steel Ceilings and Sidewalls completely satisfy the demand for a noncombustible, decorative and durable interior finish for all buildings of the higher type, whether public, churches, theaters, court houses, business blocks, stores, shops, etc., or private residences, garages, etc.

The favor with which Berger's "Classik" Steel Ceilings are regarded in this country and abroad has stimulated us to higher artistic efforts. Architects, builders and owners who desire the most artistic and durable finish for the interiors of their buildings will be sure to appreciate and profit by our endeavors.

The growth and development of the steel ceiling industry proves that the public has been prompt to appreciate and utilize the advantages of ceilings and sidewalls which are ornamental in design, perfect in construction, and combine safety with durability and satisfactory service. Not only does this hold good with new buildings, but the protest of the public is further expressed in the thousands of lath and plaster ceilings which are annually being replaced with Berger's "Classik" Steel Ceilings and Sidewalls.



Special Attention Given to the Appropriate Treatment of Interiors of Churches, Halls, Theaters, Auditoriums, Etc.

We have a full series of appropriate patterns and trimmings for all types of buildings in the prevailing style of architecture.


In many instances the construction of a Berger's "Classik" Steel Ceiling has greatly improved the acoustic properties of Churches, Halls, Auditoriums, etc.


Our designers are at your command, and submission drawings with estimates are furnished gratuitously to interested parties. Every proposition, regardless of its magnitude, is given careful attention in the selection of patterns and trimmings, and the most desirable arrangement of same, for best results and the most artistic effect.

For an estimate, send complete diagram of ceiling with measurements given as accurately as possible. State the height of ceiling and distance above doors and windows

If metal wall finish is desired, make complete diagram of each wall and measure accurately. Show location and size of doors and windows by giving necessary measurements

What is the architectural style of your building?









CEILINGS, SIDEWALLS AND COLUMNS—HOLY CROSS CATHEDRAL, BALTIMORE, MD.



I. O. O. F. LODGE ROOM, DES MOINES, IOWA




HABERDASHERY




F. W. WOOLWORTH CO., CANTON, OHIO



JEWELRY STORE




PROSCENIUM ARCH



VIEW OF PROSCENIUM ARCH AND STAGE—ALHAMBRA THEATRE, BEAVER FALLS, PA

VIEW OF BOXES, COLUMNS AND BALCONY FINISH—ALHAMBRA THEATRE, BEAVER FALLS, PA.



PROSCENIUM ARCH IN THE CARLISLE OPERA HOUSE, CARLISLE, PA.



Plate No. 4064 (½ inch deep); Multiple, 24 inches; 24 x 48 inches, 24 x 24 inches, 81/2c sq. ft.



Plate No. 4060 (1/2 inch deep), Multiple, 24 inches, 24 x 48 inches, 24 x 24 inches, 8½c sq. ft.



Plate No. 4065 (1/2 inch deep); Multiple, 24 inches 24 x 48 inches, 24 x 24 inches, 81/2c sq. ft.

Stucco




Plate No. 4068 (1/2 inch deep); Multiple, 24 inches; 24 x 48 inches, 24 x 24 inches, 81/2c sq. ft.

No. 4062



Plate No. 4062 (1/2 inch deep), Multiple, 24 inches 24 x 48 inches, 24 x 24 inches, 8½c sq. ft.

Stucco

Stucco


No. 4066

No. 4064



Plate No. 4066 (1/2 inch deep); Multiple, 24 inches. 24 x 48 inches, 24 x 24 inches, 8 1/2c sq. ft.





Flush Back Panel No. 4505—(1/8 inch deep); 24 x 24 x 48 inches; 24 x 24 inches; 8 1/3c sq. ft.

18 x 24 inches; 10c sq. ft. 18 x 18 x 54 inches; 18 x 18 inches; 10½c sq. ft.

Colonial

No. 4059



Flush Back Panel No. 4059—(½ inch deep); Multiple, 12 inches; 24 x 48 inches; 24 x 24 inches; 12 x 48 inches; 12 x 24 inches; 8c sq. ft.



Flush Back Panel No. 4056—(% inch deep); 24 x 24 x 48 inches; 24 x 24 inches; 8c sq. ft. 12 x 24 inches; 12 x 24 x 88 inches; 9c sq. ft. 24 x 24 x 34 inches; 45° angle; 24c each. 12 x 12 inches, 12c sq. ft.

Stucco

Colonial

No. 4381



Plate No. 4381; Multiple, 24 inches; 24 x 48 inches; 24 x 24 inches; 8c sq. ft.



Flush Back Panel No. 4179 – (78 inch deep); Multiple 24 inches, 24 x 48 inches, 24 x 24 inches, 8½c sq. ft.

Colonial

Colonial


No. 4055



Flush Back Panel No 4055—(12 inch deep), Multiple 12 inches, 24 x 48 inches, 24 x 24 inches, 12 x 48 inches, 12 x 24 inches, 8c so ft.



Continuous Panel No. 4079



Panel No. 4079; Multiple, 12 inches; 24 x 96 inches, 7½c sq. ft.

Colonial

No. 4081



Plate No. 4081; Multiple 6 inches; 24 x 48 inches, 24 x 24 inches, 8c sq. ft.

Colonial

No. 4187



Plate No. 4187; Multiple, 6 inches; 24 x 48 inches, 24 x 24 inches, 8c sq. ft.

Stucco

No. 4382A



Plate No. 4382A; 24 x 96 inches, 30 x 120 inches, 30 x 96 inches, 8½c sq. ft.





Sidewall Plate No. 4047;

24 x 48 inches

24 x 60 inches

24 x 72 inches

24 x 84 inches

24 x 96 inches

10c sq. ft.



Sidewall Plate No. 4048;

 24×48 inches,

24 x 60 inches

24 x 72 inches

24 x 84 inches

21 201 1110110

24 x 96 inches

10c sq. ft.



Sidewall Plate No. 4049,

 24×48 inches,

24 x 60 inches,

24 x 72 inches,

24 x 84 inches,

24 x 96 inches,

1 A 70 menes

10c sq ft.





LLUSTRATIONS on the preceding page represent the finished plates which

can be made up from the parts shown on this page.

We recommend that plates Nos. 4047, 4048 and 4049 be ordered when 4, 5, 6, 7 and 8-foot lengths are to be used.

The No. 4050A, B and C series should be specified when longer than 8-foot lengths are required as same can be made any length desired by using one or more plates No. 4050B (which is furnished in 4, 6 and 8-foot lengths), in connection with No. 4050A or C top or bottom finisher.



Stucco

No. 4050B



Sidewall Plate No. 4050B; 24 x 48 inches, 24 x 72 inches, 24 x 96 inches, 9c sq. ft.



Sidewall Plate No. 4050A; 24 x 24 inches, 9c sq. ft. Top and Bottom Finisher (arched) for No. 4050B.


Stucco

No. 4050C



Sidewall Plate No. 4050C; 24 x 24 inches, 9c sq. ft. Bottom or Top Finisher (square) for No. 4050B.








Molded Border No. 4061, Width, 18 inches; Length, 48 inches; Multiple, 24 inches; Mold Depth, 1% inches; List, 9c sq. ft. Molded Border No. 4063, Width, 18 inches; Length, 48 inches; Multiple, 24 inches; Mold Depth, 13/8 inches; List, 9c sq. ft.

Stucco


No. 4069



Molded Border No. 4069 Width, 18 inches; Length, 48 inches; Multiple, 24 inches; Mold Depth, 1 % inches; List, 9c sq. ft.




Stucco No. 4061



Inside Corner No. 4061; 18 x 18 inches, 25c each.


Stucco No. 4063



Inside Corner No. 4063; 18 x 18 inches, 25 cents each.

Stucco


No. 4069



Inside Corner No. 4069; 18 x 18 inches, 25c each.

Stucco

No. 4061



Outside Corner No. 4061; 24 x 24 inches, 40c each.

Stucco

No. 4063



Outside Corner No. 4063 24 x 24inches, 40c each.

Stucco

No. 4069



Outside Corner No. 4069; 24 x 24 inches, 40c each.



Ventilated Centers (Zinc)



No. 4663 (with Molding): 24 x 24 inches. \$4.00 each. No. 1705 (without Molding): 18 x 18 inches. \$3.00 each. No. 1706 (without Molding): 17-inch diam. \$3.00 each.

K. of P. Emblem (Zinc)



No. 4070; 30 x 30 inches, \$12.50 each.

Center

No. 4155D



No. 4155D; 45-inch diameter; In parts, \$24.75 each. No. 4155C; 45 inch diameter; Molding only, \$21.50 each.

Center

No. 4716A (Stee




Center No. 4716A (steel), 24 x 24 inch 70c each Center No. 4716 (steel), 20-inch diamet 85c each


32° Scottish Rite Emblem



No. 4078, 32 x 32 inches (zinc), \$35.00 each.



Molded Filler No. 4458; Widths, 6, 9, 12, 15, 18, 21, 24, 27 inches: Length, 48 inches; List, 8c sq. ft.




Molded Filler No. 4411; Widths, 12, 15, 18, 20 inches; Length, 48 inches; List, 8½c sq. ft.

Stucco

No. 4380

Stucco

No. 4377



Molded Filler No. 4380; Widths, 9, 12, 15, 18, 21, 24 inches; Length, 48 inches; List, 8½c sq. ft.



Filler No. 4377; Widths, 9, 12, 15, 18, 24, 30 inches; Length, 96 inches; List, 8c sq. ft.



Outside Corner Bead

Outside Corner Bead No. 4296; 1/2 x 1/2 inch; Length, 48 inches;

Width, 2½ inches; Depth, 34 inch; Length, 48 inches;

Width, 4 inches; Depth, 11/4 inches; Length, 48 inches;

Greek Beam Molding No. 4248

Gothic Beam Molding No. 4388;

Molding Ells, Tees and Crosses, 6c each.

List, 31/4c lin. ft.

List, 41/2c lin. ft.

List, 6c lin. ft.

No. 429

Inside Corner Bead No. 4295; ½ x ½ inch; Length, 48 inches; List, 2½c lin. ft.

THE THE PARTY TO SEE TH

Greek Girder Nosing

No. 4248A

Greek Beam Molding

No. 42

Greek Girder Nosing No. 4248A; ½ x ½ inch; Projection, ½ inch; Length, 48 inches; List, 5½ c lin. ft.

Rococo Beam Molding

No. 4369

Gothic Beam Molding

No. 43

Rococo Beam Molding No. 4369; Width, 3 inches; Depth, 1 inch; Length, 48 inches; List, 4%c lin. ft.

Colonial Beam Molding

No. 4568



Molding Ells, Tees and Crosses, 5c each.

Colonial Beam Molding No. 4568; Width, 4 inches; Depth, 1½ inches; Length, 48 inches; List, 5½c lin. ft. Molding Ells, Tees and Crosses. 6c each. Foot Mold and Frieze

No. 40

Foot Mold and Frieze No. 4084, Mold Projection, 1 inch; Mold Depth, 3 inches; Filler width, 4 inches; Total width, 7 inches; Length, 48 inches; List, 81/4c lin ft.





Greek Girder Molding No. 4096. Width, 5 inches, Projection, 31/2 inches, Length, 48 inches. List, 111/2c lin. ft.

French Renaissance Beam Molding

No. 4613



French Renaissance Beam Molding No. 4613 Width, 6 inches, Depth, 13/4 inches, Length, 48 inches, List, 81/4c lin ft. Molding Ells, Tees and Crosses &c each


Romanesque Beam Molding

No. 4524



Romanesque Beam Molding No. 4524; Width, 9 inches, Depth, 2 inches, Length, 48 inches; List, 10c lin. ft. Molding Ells, Tees and Crosses, 12c each

Stucco Beam Molding



Stucco Beam Molding No. 4071: Width, 51/2 inches; Depth, 13/8 inches; Length, 48 inches; List, 71/2c lin. ft.

Molding Ells, Tees and Crosses, 8c each.

Stucco Beam Molding

No. 4082




Stucco Beam Molding No. 4082 Width, 6 inches; Depth, 2 inches; Length, 48 inches; List, 11c lin. ft.

Molding Ells, Tees and Crosses, 75c each.

Colonial Beam Soffit Cover

No. 4085

Finisher 4086



Colonial Beam Soffit Cover No. 4085: Width, 9 inches; Length, 48 inches; List. 10c lin. ft. Width, 12 inches; Length, 48 inches; List, 12c lin ft.



Finisher No. 4086: Width, 9 inches: List, 121/2c each. Width, 12 inches: List 16c each



Greek Cornice Mold

No. 4:

Greek Cornice Mold No. 4290 Depth, 1% inches; Projection, 1% inches; Length, 48 inches; List, 4% lin, ft.

Greek Cornice Mold No. 4335; Depth, 3 inches; Projection, 3 inches; Length, 48 inches; List, 51/c lin. ft.

Renaissance Cornice

No. 4251C

Stucco Cornice

No. 4

Renaissance Cornice No. 4251C; Depth, 5 inches; Projection, 3½ inches; Length, 48 inches; List, 7½c lin. ft.

Cornice Mitre Leaves, 35c each.

List, 9c lin. ft.

Stucco Cornice No. 4077;
Depth, 5 inches; Projection, 5 inches; Length, 48 inches

Cornice Mitres, 60c each, Mitre Leaves, 40c each.

Romanesque Cornice

No. 4094

Greek Cornice

No. 4

Cornice Mitres, 75c each.

Romanesque Cornice No. 4094; Depth, 6 inches; Projection, 6 inches; Length, 48 inches; List, 12c lin. ft.

Greek Cornice No. 4095;

Depth, 6 inches; Projection, 4 inches; Length, 48 inche List, 10½c lin. ft.

Cornice Mitres, 60c each.



Colonial Cornice

No. 4494



Empire Cornice No. 4469.

Depth, 4 inches, Projection, 4 inches, Length, 48 inches List 7½c lin ft.

Cornice Mitres 35c each

Colonial Cornice No. 4574



Colonial Cornice No. 4574; Depth, 6 inches; Projection, 6 inches; Length, 48 inches; List, 11c lin. ft.

Cornice Mitres 40c each Mitre Leaves, 40c each

Colonial Cornice

No. 4557A



Colonial Cornice No. 4557A.

Depth, 9 inches, Projection, 7 inches, Length, 48 inches, List, 13½c lin ft.


Cornice Mitres, 60c each, Mitre Leaves, 40c each.

Colonial Cornice No. 4494; Depth, 12 inches; Projection, 9 inches; Length, 48 inches; List, 18c lin. ft.

Cornice Mitres, 75c each.

Roman Cornice

No. 4552



Roman Cornice No. 4552; Depth, 18 inches; Projection, 12 inches; Length, 48 inches; List, 22c lin. ft. Cornice Mitre Leaves, 45c each.



Colonial Cornice

No. 409




Colonial Cornice No. 4093; Depth, 8 inches; Projection, 6 inches; Length, 48 inches; List, 14c lin. ft. Cornice Mitres, 85c each. Colonial Cornice No. 4092.
Depth. 9 inches. Projection. 7 inches,
Length, 48 inches;
List. 16c lin. ft.
Cornice Mitres. 85c each

Stucco Cornice

No. 4072

Stucco Cornice

No. 406




Stucco Cornice No. 4072; Depth. 12 inches; Projection, 12 inches; Length, 48 inches; List, 21c lin. ft. Cornice Mitres, 75c each.

Stucco Cornice No. 4067,
Depth. 12 inches, Projection, 12 inches,
Length, 48 inches,
List, 21c lin. ft
Cornice Mitres, 75c each



Continuous Panel Design No. 5429



SPECIFICATIONS: Cornice Mold No. 4335 — (3 inches deep). 5½c lin. ft.; Field Panel No. 4079, 7½c sq. ft. No Cornice Mitres furnished for Cornice Mold No. 4335.




PRICE LIST

Bead Lap Joint Construction


Size of Room	Per Square
20x60 ft.	\$ 9.25
18x40 ft.	9.40
18x25 ft.	9.60
15x20 ft.	9.75
12x15 ft.	10.00

Cornice Mitre Leaves 35c each extra



SPECIFICATIONS: Cornice No. 4251C—(5 inches deep), $7\frac{1}{2}c$ lin. ft.; Filler No. 4377, 8c sq. ft., Field Panel No. 4505, $8\frac{1}{2}c$ sq. ft.





PRICE LIST

Bead Lap Joint Construction

Size of Room	Per Square
20x60 ft.	\$ 9.35
18x40 ft.	9.50
18x25 ft.	9.70
15x20 ft.	9.85
12x15 ft.	10.10

Cornice Mitres 75c each extra

SPECIFICATIONS: Cornice No. 4072—(12 inches deep), 21c lin. ft.; Molded Filler No. 4380, 8½c sq. ft.; Field Panel No. 4505, 8½c sq. ft.



PRICE LIST

Bead Lap Joint Construction


Size of Room	Per
20x60 ft.	\$ 9.25
18x40 ft.	9.40
18x25 ft.	9.60
15x20 ft.	9.75
12x15 ft.	10.00

Cornice Mitres 85c each extra



SPECIFICATIONS: Cornice No. 4093—(8 inches deep). 14c lin. ft.; Filler No. 4377, 8c sq. ft.; Field Panel No. 4179, 8½c sq. ft.





PRICE LIST

Bead Lap Joint Construction

Size of	Per
Room	Square
20x60 ft.	\$ 9.35
18x40 ft.	9.50
18x25 ft.	9.70
15x20 ft.	9.85
12x15 ft.	10.10

Cornice Mitres 75c each extra

SPECIFICATIONS: Cornice No. 4067—(12 inches deep), 21c lin. ft.; Molded Filler No. 4411, 8½c sq. ft.; Field Panel No. 4179, 8½c sq. ft.




PRICE LIST

Bead Lap Joint Construction

Size of Room	Per Square
20x60 ft.	\$8.80
18x40 ft.	9.00
18x25 ft.	9.25
15x20 ft.	9.40
12x15 ft.	9.75


Cornice Mitres 40c each extra

Cornice Mitre Leaves 40c each extra



SPECIFICATIONS: Cornice No. 4574—(6 inches deep), 11c_lin_ft; Filler No. 4377, 8c sq_ft, Field Panel No. 4055—(flush back), 8c sq_ft.





PRICE LIST

Bead Lap Joint Construction

Size of Room	Per Square
20x60 ft.	\$9.00
18x40 ft.	9.20
18x25 ft.	9.40
15x20 ft.	9.60
12x15 ft.	9.85

Cornice Mitres 60c each extra

Cornice Mitre Leaves 40c each extra

SPECIFICATIONS: Cornice No. 4557A—(9 inches deep), 13½c lin. ft.; Molded Filler No. 4380, 8½c sq. ft.; Field Panel No. 4055—(flush back), 8c sq. ft.




PRICE LIST

Bead Lap Joint Construction


Size of	Per
Size of Room	Square
20x60 ft.	\$ 9.40
18x40 ft.	9.65
18x25 ft.	10.00
15x20 ft.	10.40
12×15 ft	10 90

Cornice Mitres 85c each extra



SPECIFICATIONS: Cornice No. 4092—(9 inches deep), 16c lin. ft., Filler No. 4377, 8c sq. ft;
Beam Mold No. 4388, 6c lin. ft.
Field Panel No. 4055—(flush back), 8c sq. ft.





PRICE LIST

Bead Lap Joint Construction

Size of	Per
Room	Square
20x60 ft.	\$8.80
18x40 ft.	9.00
18x25 ft.	9.25
15x20 ft.	9.40
12x15 ft.	9.75

Cornice Mitres 40c each extra

Cornice Mitre Leaves 40c each extra

SPECIFICATIONS: Cornice No. 4574—(6 inches deep), 11c lin. ft.; Filler No. 4377, 8c sq. ft.; Field Panel No. 4056—(flush back), 8c sq. ft.



PRICE LIST

Bead Lap Joint Construction

Size of Room	Per Square
20x60 ft.	\$9.00
18x40 ft.	9.20
18x25 ft.	9.40
15x20 ft.	9.60
12x15 ft.	9.85


Cornice Mitres 60c each extra

Cornice Mitre Leaves 40c each extra



SPECIFICATIONS: Cornice No. 4557A—(9 inches deep), 133/sc lin. ft.. Molded Filler No. 4380, 83/sc sq. ft.; Field Panel No. 4056—(flush back), 8c sq. ft.





PRICE LIST

Bead Lap Joint Construction

Size of	Per
Room	Square
20x60 ft.	\$ 9.75
18x40 ft.	10.25
18x25 ft.	11.00
15x20 ft.	11.50
12x15 ft.	12.00

Cornice Mitres 75c each extra

SPECIFICATIONS: Cornice No. 4494—(12 inches deep), 18c lin. ft.; Filler No. 4382A, 8½c sq. ft.; Beam Molding No. 4082, 11c lin. ft.; Beam Molding Ell, No. 4082, 75c each; Field Panel No. 4056—(flush back), 8c sq. ft.




PRICE LIST

Bead Lap Joint Construction

Per Square Average list \$11.00


List Price will vary proportionately with the larger or smaller quantity of field plates used.

> Cornice Mitre Leaves 45c each extra



SPECIFICATIONS: Cornice No. 4552—(18 inches deep), 22c lin. ft.; Filler No. 4377, 8c sq. ft.; Beam Molding No. 4524, 10c lin. ft.; Beam Molding Ells, No. 4524, 12c each; Field Panel No. 4258—(3 inches deep), 11c sq. ft.





PRICE LIST

Bead Lap Joint Construction

> Per Square

Average list \$12.00

List Price will vary proportionately with the larger or smaller quanity of field plates used.

> Cornice Mitres 75c each extra

SPECIFICATIONS: Cornice No. 4494—(12 inches deep), 18c lin. ft.; Filler No. 4382A, 8½c sq. ft.; Beam Molding No. 4082, 11c lin. ft.; Beam Molding Ells No. 4082, 75c each; Field Panel No. 4258, 11c sq. ft.




PRICE LIST

Bead Lap Joint Construction


Size of Room	Per Square
20x60 ft.	\$ 9.25
18x40 ft.	9.40
18x25 ft.	9.60
15x20 ft.	9.75
12x15 ft.	10.00

Cornice Mitres 85c each extra



SPECIFICATIONS: Cornice No. 4093—(8 inches deep), 14c lin. ft. Filler No. 4377, 8c sq. ft.; Field Panel No. 4059, 8c sq. ft.





PRICE LIST

Bead Lap Joint Construction

Size of Room	Per Square
20x60 ft.	\$ 9.35
18x40 ft.	9.50
18x25 ft.	9.70
15x20 ft.	9.85
12x15 ft.	10.10

Cornice Mitres 60c each extra

Cornice Mitre Leaves 40c each extra

SPECIFICATIONS: Cornice No. 4557A—(9 inches deep), 13½c lin. ft.;
Molded Filler No. 4411, 8½c sq. ft.;
Field Panel No. 4059—(flush back), 8c sq. ft.




PRICE LIST

Bead Lap Joint Construction


Size of Room	Per Square
20x60 ft.	\$8.85
18x40 ft.	9.10
18x25 ft.	9.30
15x20 ft.	9.60
12x15 ft.	9.90

Cornice Mitre Leaves 35c each extra



SPECIFICATIONS: Cornice No. 4251C—(5 inches deep), 7½c lin. ft. Molded Filler No. 4411, 8½c sq. ft.; Field Plate No. 4081, 8c sq. ft.





PRICE LIST

Bead Lap Joint Construction

Size of Room	Per
Room	Square
20x60 ft.	\$8.80
18x40 ft.	9.00
18x25 ft.	9.25
15x20 ft.	9.40
12x15 ft.	9.75

Cornice Mitres


SPECIFICATIONS: Cornice No. 4095—(6 inches deep), 10½c lin ft; Filler No. 4377, 8c sq ft; Field Plate No. 4187, 8c sq ft.



PRICE LIST Bead Lap Joint Construction


Size of Room	Per Square
20x60 ft.	\$8.90
18x40 ft.	9.10
18x25 ft.	9.30
15x20 ft.	9.50
12x15 ft.	9.75

Cornice Mitres 75c each extra



SPECIFICATIONS: Cornice No. 4094—(6 inches deep), 12c lin. ft.; Molded Filler No. 4380, 8½c sq. ft.; Field Plate No. 4381, 8c sq. ft.





PRICE LIST

Bead Lap Joint Construction

Size of Room	Per Square
20x60 ft.	\$ 9.00
18x40 ft.	9.20
18x25 ft.	9.40
15x20 ft.	9.65
12x15 ft.	10.00

Cornice Mitres

Cornice Mitre Leaves 40c each extra

SPECIFICATIONS: Cornice No. 4077—(5 inches deep), 9c lin. ft.; Field Plate No. 4382A, 8½c sq. ft.



PRICE LIST


Bead Lap Joint Construction

Per Square
Average list \$14.50

List price will vary proportionately with the quantity of larger or smaller spacings between beam moldings.

> Cornice Mitres 60c each extra


Cornice Mitre Leaves 40c each extra



SPECIFICATIONS: Cornice No. 4077—(5 inches deep), 9c lin. ft.; Beam Molding No. 4082, 11c lin. ft.; Beam Molding Ells. Tees and Crosses No. 4082, 75c each; Field Plate No. 4382A, 8½c sq. ft.

(Cut shows 4 x 5 feet, spacing between Beam Moldings.)





PRICE LIST

Size of	Per
Room	Square
20x60 ft.	\$14.25
18x40 ft.	15.00
18x25 ft.	15.50
15x20 ft.	16.00
12x15 ft.	17.00

Note—These list prices will vary proportionately with the quantity of larger or smaller spacings between beam moldings.

SPECIFICATIONS: Cornice Mold No. 4290—(1¾ inches deep), 4½c lin. ft.; ¾ Beam Molding No. 4082A, 9c lin. ft.; Full Beam Molding No. 4082, 11c lin. ft.; Beam Molding Ells and Tees No. 4082, 75c each; Field Plate No. 4382A, 8½c sq. ft.

(Cut shows 30 inches spacing between Beam Moldings.)




SPECIFICATIONS

Cornice No. 4093-(8 inches deep), 14c lin. Molded Filler No. 4380, 81/2c sq. ft.; 3/4 Beam Molding No. 4082A, 9c lin. ft.; Full Beam Molding No. 4082, 11c lin. ft.; Beam Molding Ells No. 4082, 75c each; Border Panels No. 4505, 18 x 24 inches, 10c sq. ft.; 18 x 18 inches, 101/20 sq. ft.; Field Plate No. 4382A. 8½c sq. ft.


PRICE LIST

Average list price for room 22'x22' or larger, \$16.60 per square.

Cornice Mitres 85c each extra







SPECIFICATIONS

Cornice No. 4093-(8 inches deep), 14c lin. ft :: Molded Filler No. 4380, 81/2c sq. ft.: 34 Beam Molding No. 4082A, 9c lin. ft.; Full Beam Molding No. 4082, 11c lin. ft.: Beam Molding Ells No. 4082, 75c each; Border Panels No. 4505. 18 x 24 inches. 10c sq. ft.; 18 x 18 inches, 10½c sq. ft.; Field Plate No. 4382A, 81/2c sq. ft.

PRICE LIST

Average list price for room 14'x14' or larger, \$16.40 per square.

Cornice Mitres 85c each extra




PRICE LIST

Average list price for room 22'x22' or larger, \$13.00 per square.


> Cornice Mitres 60c each extra

Cornice Mitre Leaves 40c each extra



SPECIFICATIONS: Cornice No. 4077—(5 inches deep), 9c lin. ft.; Beam Molding No. 4613, 81/4c lin. ft.; Curved Molding No. 4639, 75c each: Molded Filler No. 4380, 8½c sq. ft.; Inner Field Plate and Outer Field Plate No. 4382A, 81/2c sq. ft.





PRICE LIST

Average list price for room 14'x14' or larger, \$13.00 per square.

Cornice Mitres 60c each extra

Cornice Mitre Leaves 40c each extra

SPECIFICATIONS: Cornice No. 4077—(5 inches deep), 9c lin. ft.; Beam Molding No. 4613, 8½c lin. ft.; Curved Molding No. 4639, 75c each; Molded Filler No. 4380, 8½c sq. ft.; Inner Field Plate and Outer Field Plate No. 4382A, 8½c sq. ft.




PRICE LIST

Bead Lap Joint Construction

Size of	Per
Room	Square
20x60 ft.	\$ 9.15
18x40 ft.	9.40
18x25 ft.	9.60
15x20 ft.	9.85
12x15 ft.	10 25


Cornice Mitres 60c each extra

Cornice Mitre Leaves 40c each extra



SPECIFICATIONS: Cornice No. 4557A.—(9 inches deep), $13\frac{1}{2}$ c lin. ft.; Molded Filler No. 4458. 8c sq. ft.; Border Panel No. 4056, 12×24 inches, 9c sq. ft.; 12×12 inches, 12c sq. ft.; Field Plate No. 4382A, $8\frac{1}{2}$ c sq. ft.





PRICE LIST

Bead Lap Joint Construction

Size of Room	Per Square
20x60 ft.	\$ 9.40
18x40 ft.	9.65
18x25 ft.	10.00
15x20 ft.	10.40
12x15 ft.	10.90

Cornice Mitres 75c each extra

SPECIFICATIONS: Cornice No. 4067—(12 inches deep), 21c lin. ft.; Filler No. 4377, 8c sq. ft.; Molded Border No. 4061, 9c sq. ft.; Inside Corners No. 4061, 25c each; Field Plate No. 4060, 8½c sq. ft.




PRICE LIST

Bead Lap Joint Construction

Size of Room	Per
Room	Square
20x60 ft.	\$ 9.40
18x40 ft.	9.65
18x25 ft.	10.00
15x20 ft.	10.40
12x15 ft.	10 90

Cornice Mitres 60c each extra


Cornice Mitre Leaves 40c each extra



SPECIFICATIONS: Cornice No. 4557A—(9 inches deep), 13½c lin. ft.; Filler No. 4377, 8c sq. ft. Molded Border No. 4061, 9c sq. ft.; Inside Corner No. 4061, 25c each; Field Plate No. 4064, 8½c sq. ft.



Stucco Effect – Design No. 5464



PRICE LIST

Bead Lap Joint Construction

Size of Room	Per Square
20x60 ft.	\$ 9.40
18x40 ft.	9.65
18x25 ft.	10.00
15x20 ft.	10.40
12x15 ft.	10.90

Cornice Mitres 75c each extra

SPECIFICATIONS: Cornice No. 4072—(12 inches deep), 21c lin. ft.; Filler No. 4377, 8c sq. ft.; Molded Border No. 4061, 9c sq. ft.; Inside Corner No. 4061, 25c each. Field Plate No. 4065, 8½c sq. ft.



Stucco Effect – Design No. 5465


PRICE LIST

Bead Lap Joint Construction

Size of Room	Per Square
20x60 ft.	\$ 9.40
18x40 ft.	9.65
18x25 ft.	10.00
15x20 ft.	10.40
12x15 ft.	10.90

Cornice Mitres 60c each extra


Cornice Mitre Leaves 40c each extra



SPECIFICATIONS: Cornice No. 4557A—(9 inches deep), 13½c lin. ft; Filler No. 4377, 8c sq. ft. Molded Border No. 4063, 9c sq. ft; Field Plate No. 4062, 8½c sq. ft.



Stucco Effect — Design No. 5466



PRICE LIST

Bead Lap Joint Construction

Size of	Per
Room	Square
20x60 ft.	\$ 9.40
18x40 ft.	9.65
18x25 ft.	10.00
15x20 ft.	10.40
12x15 ft.	10.90

Cornice Miters 75c each extra

SPECIFICATIONS: Cornice No. 4072—(12 inches deep), 21c lin. ft.; Filler No. 4377, 8c sq. ft.; Molded Border No. 4069, 9c sq. ft.; Inside Corner No. 4069, 25c each; Field Plate No. 4068, 8½c sq. ft.




Stucco Effect - Design No. 5467

PRICE LIST

Bead Lap Joint Construction

Size of	Per
Room	Square
20x60 ft.	\$ 9.50
18x40 ft.	9.75
18x25 ft.	10.10
15x20 ft.	10.50
12x15 ft.	11.00


Cornice Mitre Leaves 45c each extra



SPECIFICATIONS: Cornice No. 4552—(18 inches deep), 22c lin. ft.; Filler No. 4377, 8c sq. ft.; Beam Molding No. 4071, 7½c lin. ft.; Beam Molding Ells, 8c each; Field Plate No. 4066, 8½c sq. ft.



Stucco Effect - Design No. 5468



PRICE LIST

Bead Lap Joint Construction

Sec.	#		٥	
Dudd	b.		*	MI
8,40	Ba.			81
Nu23			10	900
14,20	for.		10	80
				100

Carreira Mitrea Ple sach satra

SPECIFICATIONS: Carnice No. 4062—(12 inches despt. 25s lin. 5t.; Filter No. 4227, 8s eq. 5t.; Madded Barder No. 4062, 9s eq. 5t.; Inside Carner No. 4062, 25s each: Field Places Nos. 4062 and 4064 Alternating, 81;c eq. 5t.




Stucco Effect - Design No. 5469

PRICE LIST

Bead Lap Joint Construction

Size of Room	Per Square
Room	Square
20x60 ft.	\$ 9.40
18x40 ft.	9.65
18x25 ft.	10.00
15x20 ft.	10.40
12x15 ft.	10.90


Cornice Mitres 75c each extra



SPECIFICATIONS: Cornice No. 4067—(12 inches deep), 21c lin ft; Filler No. 4377, 8c sq. ft; Molded Border No. 4061, 9c sq. ft; Inside Corner No. 4061, 25c each; Field Plates Nos. 4064 and 4065 Alternating, 8½c sq. ft



Stucco Effect – Design No. 5470



PRICE LIST

Bead Lap Joint Construction

Size of Room	Per Square
20x60 ft.	\$ 9.40
18x40 ft.	9.65
18x25 ft.	10.00
15x20 ft.	10.40
12x15 ft.	10.90

Cornice Mitres 75c each extra

SPECIFICATIONS: Cornice No. 4067—(12 inches deep), 21c lin. ft.; Filler No. 4377, 8c sq. ft.; Molded Border No. 4061, 9c sq. ft.; Inside Corner No. 4061, 25c each; Field Plates Nos. 4060 and 4065 Alternating, 8½c sq. ft.



SPECIFICATIONS

Cornice No. 4067— (12 inches deep), 21c lin. ft.;


Sidewall Plate No. 4049 — (24 inches wide), 10c sq. ft.;

Chair Mold No. 4071
—(5½ inches wide),
7½c lin. ft.;

Wainscot No. 4616— (24 x 34 inches), 9c sq. ft.

When longer than eight-foot sheets of No. 4049 are required same will be furnished in parts No. 4050A, B and C. See page 27.





SPECIFICATIONS

Cornice No. 4067— (12 inches deep), 21c lin. ft.;

Sidewall Plate No. 4048—(24 inches wide), 10c sq. ft.;

Chair Mold No. 4071
—(5½ inches wide),
7½c lin. ft.;

Wainscot No. 4616— (24 x 34 inches), 9c sq. ft.

When longer than eight-foot sheets of No. 4048 are required same will be furnished in parts No. 4050A, B and C. See page 27

SPECIFICATIONS


Cornice No. 4067— (12 inches deep), 21c lin. ft.;

Frieze or Plate No. 4048 (24 x 48 inches), 10c sq. ft.:

Sidewall Plate No. 4049—(24 inches wide), 10c sq. ft.

When longer than eight-foot sheets of No. 4049 are required same will be furnished in parts No. 4050A, B and C. See page 27.





SPECIFICATIONS

Cornice No. 4067— (12 inches deep), 21c lin. ft.;

Frieze or Plate No. 4048—(24 x 48 inches) 10c sq. ft.;

Sidewall Plate No. 4048—(24 inches wide), 10c sq. ft.

When longer than eight-foot sheets are required same will be furnished in parts No. 4050A, B and C. See page 27.


SPECIFICATIONS

Cornice No. 4067— (12 inches deep), 21c lin. ft.;

Sidewall Plate No. 4049—(24 inches wide), 10c sq. ft.;

When longer than eight-foot sheets are required same will be furnished in parts No. 4050A, B and C. See page 27.





SPECIFICATIONS

Cornice No. 4067— (12 inches deep), 21c lin. ft.;

Sidewall Plate No. 4048—(24 inches wide), 10c sq. ft.

When longer than eight-foot sheets are required same will be furnished in parts No. 4050A, B and C. See page 27.

Index and Telegraph Code

Questions, Inquiries and Commands

Wire price on	Ship by express
---------------	-----------------

Quotations, Answers, Etc.

	Your order of——was shipped by freight	mationy k ba cic re aller bage
--	---------------------------------------	--------------------------------

No.	Description	Price	Page	Code	No.	Description	Price	Page	Code
1705	Center 18 x 18"	\$3.00	30	Capon	4049	Wall Plate 24 x 84"	\$.10	26	Carabus
1706	" 17" diameter	3.00	30	Capsize	4049	" 24 x 96"	.10	26	Carac
4047	Wall Plate 24 x 48"	.10	26	Captivity	4050A	" 24 x 24" Per sq. ft.	.09	27	Caracal
4047	" " 24 x 60"	.10	26	Captor	4050B	" 24 x 48" Per sq. ft	.09	27	Carack
4047	" " 24 x 72"	.10	26	Capture	4050B	" 24 x 72" Per sq. ft.	.09	27	Caracole
4047	" " 24 x 84"	.10	26	Capuccio	4050B	" 24 x 96"Per sq. ft.	.09	27	Caracore
4047	" " 24 x 96"Per sq. ft.	.10	26	Capuched	4050C	" 24 x 24" Per sq. ft.	.09	27	Carageen
4048	" " 24 x 48"	.10	26	Capucine	4055	Panel 24 x 24 x 48"Per sq. ft.	.08	24	Carambola
4048	" " 24 x 60"Per sq. ft.	.10	26	Capulet	4055	" 24 x 24"	.08	24	Caramel
4048	" " 24 x 72"	.10	26	Capulin	4055	" 12 x 24 x 48"Per sq. ft.	.08	24	Carangoid
4048	" " 24 x 84"	.10	26	Caput	4055	12 x 24"	.08	24	Caranx
4048	" " 24 x 96"	.10	26	Carabid	4056	24 x 24 x 48"	.08	24	Carapace
4049		.10	26	Carabine	4056	24 x 24"	.08	24	Carapox
4049	" " 24 x 60"	.10	26	Carabineer	4056	" 12 x 24 x 48"	.09	24	Carat
4049	" " 24 x 72"Per sq. ft.	.10	26	Caraboid	4056	" 12 x 24"Per sq. ft.	.09	24	Caravan



Index and Telegraph Code—Continued

No.	Description	Price	Page	Code	No.	Description	Price	Page	Code
	D 110 100	A 12	24	Caravel	4084	Molding, length 48"	\$.081/4	32	Carol
056	Panel 12 x 12" Per sq. ft	\$ 12	24		4085	Beam Soffit 9 x 48"	.10	33	Carolus
)56	" 24 x 24 x 34" Eac		24	Caraway		12 x 48" Per lin ft.	.12	33	Carporal
)59	24 X 24 X 40	. 08	24	Cardinalize	4085	12 x 40 Fer III. It.		33	Carometer
)59	" 24 x 24" Per sq. ft	. 08	24	Cardiograph	4086	Finisher 9 x 6"Each	16/2	33	
059	" 12 x 24 x 48" Per sq. ft	. 08	24	Cardioid	4086	12 x 6" Each Cornice, length 48" Per lin. ft.	.16	36	Cartesan
)59	" 12 x 24"	.08	24	Cardo	4092	Cornice length 48" Per lin. ft.	.16		Carpet
060	Plate 24 x 48 Per sq. ft	081/2	23	Cardol	4092	Inside Mitre Each		36	Carping
60	" 24 x 24" Per sq. ft		23	Cardoon	4092	Outside Mitre Each Cornice, length 48" Per lin. ft.	.85	36	Carpolite
100	Border 18 x 48" Per sq. ft		28	Careenage	4093	Cornice length 48" Per lin. ft.	.14	36	Carouse
	Border 10 x 40		29	Caressingly	4093	Inside Mitre Each	.85	36	Carousal
)61	Inside Corner 18 x 18"		29		4093	Outside Mitre Each	.85	36	Carrion
61	Outside Corner 24 x 24" Eac	40	29	Caret		Outside Mitre Each Cornice, length 48" Per lin. ft.	.12	34	Carrier
)62	Plate 24 x 48' Per sq. f	. 081/2	23	Careworn	4094	Inside Mitre Each	75	34	Carrom
062			23	Carex	4094	Inside Mitre		34	Carroty
063	Border 18 x 48" Per sq. fi	. 09	28	Carf	4094	Outside Mitre Each	101/2	34	Carrot
063	Inside Corner 18 x 18" Eac	25	29	Cargason	4095	Cornice length 48"		34	
063	Outside Corner 24 x 24" Eac	40	29	Cargoose	4095	Inside Mitre Each	.60		Carrow
	Plate 24 x 48" Per sq. f	081/2	23	Cariama	4095	Outside MitreEach	.60	34	Catartus
64	" 24 x 24" Per sq. f	081/2	23	Carib	4096	Molding length 48"	111/2	33	Cartoon
	" 24 x 48" Per sq. f		23	Caribbean	41550	Center, 45" diameter Each	21.50	30	Confederacy
)65			23	Caribbean	4155E		24.75	30	Confederati
65			23	Caribon	4170	Panel 24 x 24 x 48"	.081/2	24	Obdek
66		081/2	23		4179	24 x 24"	.081/2	24	Oddag
66	" 24 x 24" Per sq. ft	. 081/2	23	Caricature		Plate 24 x 48" Per sq. ft.	.08	25	Obeliscal
067	Cornice, length 48" Per lin. f	. 21	36	Caricous	4187	Plate 24 x 40	.08	25	Obelion
067	Inside Mitre Eac	1 .75	36	Carillon	4187	24 x 24"	041/2	32	Omnoy
067	Outside Mitre Eac	75	36	Carina	4248	Molding length 48" Per lin. ft.	051/2	32	Omofo
068	Plate 24 x 48 Per sq. f	. 081/2	23	Carinaria	4248A	Girder Nosing length 48" Per lin. ft.		34	
068	" 24 - 24' Per sq f	081/2	23	Cariole	42510	Cornice length 48" Per lin. It.	.071/2		Onset
069	" 24 x 24" Per sq f Border 18 x 48" Per sq f Inside Corner 18 x 18" Eac	09	28	Cariopsis	42510	Inside Leaf Each	.35	34	Ontology
909	Dorder 10 x 40	25	29	Cariosity	42510	Outside Leaf Each	.35	34	Onvap
069	Outside Corner 24 x 24' Eac	40	29	Cark	4290	Cornice, length 48"	.04 1/2	34	Overt
069			30	Carkanet	4295	Inside Corner Bead, length 48" Per lin. ft.	.021/2	32	Oviation
070	K of P Emblem 30 x 30' Eac		33	Carlin	4296	Outside Corner Bead, length 48". Per lin. ft.	.031/4	32	Oviform
71	Molding, length 48" Per lin. f		22		4335	Cornice length 48"	.051/2	34	Pavilion
71	Ell	.08	33	Carlings		Molding, length 48"	.043/4	32	Pettish
71	Tee		33	Carlist	4369	Ell Each		32	Pervade
71	Cross	.08	33	Carmelite	4369	Ell		32	Pervit
72	Cornice length 48	. 21	36	Carminated	4369	TeeEach		32	Phaeton
72	Inside Mitre	75	36	Carnage	4369	Cross	.08	31	Pilot
72	Outside Mitre Eac	75	36	Carnation	4377	Cross Each Filler 9 x 96" Per sq. ft.			
77	Cornice Length 48 Per lin f		34	Carnelian	4377	12 x 96"Per sq. ft.	.08	31	Pillage
	Cornice Length 40		34	Carneous	4377	" 15 x 96"	.08	31	Pinafore
77	Inside Mitre Eac		34	Carney	4377	18 x 96" Per sq. ft.	.08	31	Pinched
77			34	Carnin	4377	24 x 96" Per sq. ft.	.08	31	Pinky
77	Inside Leaf Eac	40	34	Carnival	4377	" 30 x 96" Per sq. ft.	.08	31	Pirate
77	Outside Leaf Eac	1 .40			4380	9 x 48"	.081/2	31	Plenal
70	Scottish Rite Emblem 32 x 32 Eac	35.00	30	Carnivore		12 x 48"	.081/2	31	Plenarily
79	Continuous Panel 24 x 96" Per sq. ft	071/2	25	Carnivorous	4380	15 x 48"	081/2	31	Plenariness
			25	Carnosity	4380	15 x 48 Per sq. ft.	081/2	31	Plenicorn
81	" 24 x 24" Per sq. ft	. 08	25	Caroche	4380	10 X 40	.081/2	31	Plenilunary
82	Malding langth 48' Per lin ft	.11	33	Cardinate	4380	" 21 x 48" Per sq. ft.		31	
02	" 24 x 24" Molding, length 48' Per sq. ft Per lin ft Eacl	75	33	Carding	4380	24 x 48"	.081/2		Plenipotent
04	- III		33	Cardiology	4381	Plate 24 x 48"Per sq. ft.	.08	24	Plenilune
82	Tee Eac		33	Cardiometry	4381	24 x 24"	.08	24	Pleno



Index and Telegraph Code—Concluded

No.	Description	Price	Page	Code	No.	Description	Price	Page	Code
4382 A	Plate 24 x 96"	\$.081/2	25	Plinth	4574	Outside Leaf Each	\$.40	35	Shield
4382A	" 30 x 96"	.081/2	25	Plim	4613	Molding, length 48"	.081/4	33	Stalwart
1382A	" 30 x 120"	.081/2	25	Plinite	4613	Ell Each	.08	33	Stampede
	Molding, length 48"	.06	32	Pod	4613	Tee Each	.08	33	Stanch
	Ell Each	.06	32	Poetical	4613	Cross Each	.08	33	Stanza
	Tee Each	.06	32	Poison	4663	Center 24 x 24" Each	4.00	30	Sweeting
	Cross Each	.06	32	Poker	4716	" 20" diameter Each	.85	30	Vacher
	Filler 12 x 48"	.081/2	31	Prehensory	4716A		.70	30	Vacillant
411	" 15 x 48"	.081/2	31	Prehistoric	5429	Continuous Panel Design		37	Zebec
411	13 x 40 Fer sq. It.	.081/2	31	Prelacy	5430			38	Zedoary
411	10 x 40	.081/2	31	Prelatize	5431	Colonial Design		39	Zeekoe
458	20 x 48"		31					40	
458	6 x 48"	.08		Rainfall	5432	4 4		41	Zehner
458	9 x 48"	.08	31	Raininess	5433				Zenana
458	12 x 48"	.08	31	Rajah	5436	" "		42	Zibet
	15 x 48"	.08	31	Raker	5437			43	Zincous
458	" 18 x 48"	.08	31	Rakish	5438			44	Zircon
458	21 x 48"	. 08	31	Rally	5439			45	Zither
458	24 x 45	.08	31	Ramadan	5440			46	Zoba
458	" 27 x 48"	. 08	31	Ramal	5441	46 46		47	Zobebah
469	Cornice, length 48"	.07 1/2	35	Rebel	5442	44 44		48	Zodiacus
	Inside MitreEach	.35	35	Rebuff	5443			49	Zoetus
	Outside MitreEach	.35	35	Rebuke	5444	44 45		50	Zoilus
	Cornice, length 48"	.18	35	Reproach	5445	44 44		51	Zoma
494	Inside MitreEach	.75	35	Republic	5446	и и		52	Zombe
494	Outside MitreEach	.75	35	Repugnant	5447			53	Zongo
505	Panel 24 x 24 x 48"	.081/2	24	Retreatful	5448	Stucco Design		54	Zoography
505	" 24 x 24"	.081/2	24	Retrench	5449	44 14		55	Zoology
505	" 18 x 24"	.10	24	Retrograde	5450	44		56	Zoonic
505	" 18 x 18 x 54"	.101/2	24	Retrospect	5451	u u		57	Zoonomy
505	" 18 x 18"	.101/2	24	Retrovert	5452			58	Zoophago
524	Molding, length 48"	.10	33	Ropiness	5453	44		59	Zoophyte
524	EllEach	.12	33	Rostrum	5454	tt tt		60	Zootomy
524	Tee Each	.12	33	Rotunda	5455	41 41		61	Zootomist
	Cross Each	.12	33	Roulette	5456	44 44		62	Zophar
552	Cornice, length 48"	.22	35	Sanctity	5462	"		63	Zophim
552	Inside Leaf Each	.45	35	Sandfly	5463	44 44		64	Zopyrus
552	Outside Leaf Each	.45	35	Sandpipe	5464	9 9		65	Zoreah
557A	Cornice, length 48"	.131/6	35	Schoolman	5465	44		66	Zorean
557A	Inside MitreEach	.60	35	Scornful	5466				
557A	Outside Mitre	.60	35	Scottish	5467			67	Zucchi
557A	Inside Leaf Each	.40	35	Schooner	5468	-и и		68	Zululand
557A	Outside Leaf Each	.40	35	Scoff	5469			69	Zumology
568	Molding, length 48" Per lin. ft.	.051/6	32	Serpent	5470			70	Zuni
568	Ell. Each	.06	32	Setpin				71	Zurich
	Tee Each	.06	32	Sexton	5471 5472	Stucco Sidewall Design		72	Zwoole
	Cross Each	06	32	Shadbush				73	Zygena
	Cornice, length 48"	.00	35	Shadbush	5473			74	Zygomatic
	Inside MitreEach	.11			5474			75	Zylonite
	Outside Mitre Each		35	Shocked	5475			76	Zymotic
4574	Inside Leaf Each	40	35	Shoelace	5476	***************************************		77	Zythum



[BLANK PAGE]



